

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2021/0170100 A1 Lanigan et al.

Jun. 10, 2021 (43) **Pub. Date:**

(54) APPARATUS, SYSTEM AND METHOD FOR FLUID DELIVERY

(71) Applicant: **DEKA Products Limited Partnership**, Manchester, NH (US)

(72) Inventors: Richard J. Lanigan, Concord, NH (US); Dean Kamen, Bedford, NH (US);

> Bright C. K. Foo, Hollis, NH (US); Kevin L. Grant, Litchfield, NH (US); Lisa A. Gustin, Manchester, NH (US)

(21) Appl. No.: 17/177,691

(22) Filed: Feb. 17, 2021

Related U.S. Application Data

- (60) Division of application No. 15/284,030, filed on Oct. 3, 2016, now Pat. No. 10,926,030, which is a continuation of application No. 13/788,785, filed on Mar. 7, 2013, now Pat. No. 9,456,955, which is a continuation-in-part of application No. 12/649,681, filed on Dec. 30, 2009, now Pat. No. 10,188,787, which is a continuation-in-part of application No. 12/347,985, filed on Dec. 31, 2008, now Pat. No. 8,491,570, said application No. 12/649,681 is a continuation-in-part of application No. 12/347,982, filed on Dec. 31, 2008, now Pat. No. 9,526,830, said application No. 12/649, 681 is a continuation-in-part of application No. 12/347,984, filed on Dec. 31, 2008, now Pat. No. 8,414,563.
- (60) Provisional application No. 61/607,848, filed on Mar. 7, 2012, provisional application No. 61/142,042, filed on Dec. 31, 2008, provisional application No. 61/225, 794, filed on Jul. 15, 2009, provisional application No. 61/018,054, filed on Dec. 31, 2007, provisional application No. 61/018,042, filed on Dec. 31, 2007, provisional application No. 61/017,989, filed on Dec. (Continued)

Publication Classification

(51) **Int. Cl.** A61M 5/168 (2006.01)H01Q 9/26 (2006.01)

G05D 7/06	(2006.01)
A61M 5/14	(2006.01)
A61M 5/142	(2006.01)
A61M 5/172	(2006.01)
A61J 1/20	(2006.01)
H01Q 7/00	(2006.01)
$H01\tilde{Q} 1/27$	(2006.01)
$B65\tilde{B} \ 3/00$	(2006.01)
G16H 20/17	(2018.01)
G01F 11/08	(2006.01)

(52)

U.S. Cl. CPC . A61M 5/16809 (2013.01); A61M 2205/3546 (2013.01); G05D 7/0647 (2013.01); A61M 5/1413 (2013.01); A61M 5/142 (2013.01); A61M 5/172 (2013.01); A61J 1/2096 (2013.01); G05D 7/0676 (2013.01); H01Q 7/00 (2013.01); H01Q 1/273 (2013.01); A61M *5/14248* (2013.01); *B65B* 3/003 (2013.01); A61J 1/20 (2013.01); G16H 20/17 (2018.01); A61M 5/14244 (2013.01); G01F 11/086 (2013.01); A61M 2005/14268 (2013.01); A61M 2205/3368 (2013.01); A61M 2205/18 (2013.01); A61M 2205/3331 (2013.01); A61M 2205/7536 (2013.01); A61M 2205/3393 (2013.01); A61M 2205/50 (2013.01); A61M 2205/3576 (2013.01); A61M 2205/70 (2013.01); A61M 2205/59 (2013.01); A61M 2209/045 (2013.01); A61M 2205/8237 (2013.01); A61M 2205/6018 (2013.01); A61M 2209/086 (2013.01); A61M 5/16886 (2013.01); A61M 2205/3515 (2013.01); A61M 2205/3375 (2013.01); A61M 2205/3569 (2013.01); A61M 2205/0266 (2013.01); H01Q 9/265 (2013.01)

(57)ABSTRACT

A filling aid. The filling aid includes a needle housing portion including at least one tab having a starting position and a filling position, and a filling needle cradle including a filling needle, the filling needle cradle slidable connected to the needle housing portion and having a starting position and a filling position, wherein when the at least one tab on the needle housing moves from a starting position to a filling position, the filling needle cradle slides from a starting position to a filling position, and wherein when the at least one tab on the needle housing moves from a filling position to a starting position, the filling needle cradle slides from a filling position to a starting position.

